

Control de atornillador - Fuente de alimentación

Comunicación a PLC



SP-C32HL60TC

+



SERIE PLUS

=



Arranque por palanca

Rango de Par ± 3%	Velocidad libre ± 10% (r.p.m.)		Modelo	Tornillo		Peso grms	Largo mm	Alimentación
	N.m	Baja		Alta	Métrico mm			
0,02 - 0,34	1000	600	EA-C203L/C	1,0 - 2,3	1,0 - 2,0	270	205	DC20V o 32V
0,05 - 0,69	1000	600	EA-C207L/C	1,4 - 2,6	1,4 - 2,3	270	205	DC20V o 32V
0,10 - 0,98	670	400	EA-C210L/C	1,6 - 3,0	1,6 - 2,6	270	205	DC20V o 32V
0,1 - 0,78	2000		EA-C408LH/C	1,6 - 3,0	1,6 - 2,6	480	230	DC20V o 32V
0,1 - 1,18	1000	600	EA-C412L/C	1,6 - 3,0	1,6 - 2,6	480	230	DC20V o 32V
0,3 - 1,57	1000	600	EA-C416L/C	2,3 - 3,5	2,3 - 3,0	480	230	DC20V o 32V
0,2 - 0,98	2000		EA-C610LH/C	2,0 - 3,0	2,0 - 2,6	600	260	DC20V o 32V
0,5 - 1,76	1000	600	EA-C618L/C	2,0 - 3,5	2,0 - 3,0	600	260	DC20V o 32V
0,69 - 2,35	750	450	EA-C624L/C	2,6 - 4,0	2,6 - 3,5	600	260	DC20V o 32V
0,78 - 2,94	530	300	EA-C630L/C	3,0 - 5,0	3,0 - 4,0	600	260	DC20V o 32V
0,49 - 1,18	2000		EA-C712LH/C	2,3 - 3,5	2,0 - 3,0	700	269	DC20V o 32V
0,59 - 2,25	1000	600	EA-C723L/C	2,6 - 4,0	2,6 - 3,5	700	269	DC20V o 32V
0,98 - 3,14	750	450	EA-C732L/C	3,0 - 5,0	3,0 - 4,5	700	269	DC20V o 32V
1,57 - 4,70	530	300	EA-C748L/C	4,0 - 6,0	3,0 - 5,0	700	269	DC20V o 32V



Atornilladores preparados para trabajar con el controlador: Conexión de 7 pin

Arranque por empuje

Rango de Par ± 3%	Velocidad libre ± 10% (r.p.m.)		Modelo	Tornillo		Peso grms	Largo mm	Alimentación
	N.m	Baja		Alta	Métrico mm			
0,15 - 0,78	2000		EA-C408PH/C	1,6 - 3,0	1,6 - 2,6	480	230	DC20V o 32V
0,15 - 1,18	1000	600	EA-C412P/C	1,6 - 3,0	1,6 - 2,6	480	230	DC20V o 32V
0,3 - 1,57	1000	600	EA-C416P/C	2,3 - 3,5	2,3 - 3,0	480	230	DC20V o 32V
0,2 - 0,98	2000		EA-C610PH/C	2,0 - 3,0	2,0 - 2,6	600	260	DC20V o 32V
0,5 - 1,76	1000	600	EA-618P/C	2,0 - 3,5	2,0 - 3,0	600	260	DC20V o 32V
0,69 - 2,35	750	450	EA-C624P/C	2,6 - 4,0	2,6 - 3,5	600	260	DC20V o 32V
0,78 - 2,94	530	300	EA-C630P/C	3,0 - 5,0	3,0 - 4,0	600	260	DC20V o 32V
0,49 - 1,18	2000		EA-C712PH/C	2,3 - 3,5	2,0 - 3,0	700	270	DC20V o 32V
0,59 - 2,25	1000	600	EA-C723P/C	2,6 - 4,0	2,6 - 3,5	700	270	DC20V o 32V
0,98 - 3,14	750	450	EA-C732P/C	3,0 - 5,0	3,0 - 4,5	700	270	DC20V o 32V
1,57 - 4,70	530	300	EA-C748P/C	4,0 - 6,0	3,0 - 5,0	700	270	DC20V o 32V



Atornilladores preparados para trabajar con el controlador: Conexión de 7 pin