

Control de atornillador - Fuente de alimentación

Comunicación a PLC



SP-C32HL60TC

+=



SERIE PLUS



Arranque por palanca

Rango de Par ± 3%	Velocidad libre ± 10% (r.p.m.)	Modelo	Tornillo		Peso Largo mm	Alimentación
			Métrico	Auto roscante		
0,02 - 0,34	1000600	EA-C203L/C	1,0 - 2,31,0	2,0270205DC20V o 32V		
0,05 - 0,69	1000600	EA-C207L/C	1,4 - 2,61,4	2,3270205DC20V o 32V		
0,10 - 0,98	670400	EA-C210L/C	1,6 - 3,01,6	2,6270205DC20V o 32V		
0,1 - 0,78	2000	EA-C408LH/C	1,6 - 3,01,6	2,6480230DC20V o 32V		
0,1 - 1,18	1000600	EA-C412L/C	1,6 - 3,01,6	2,6480230DC20V o 32V		
0,3 - 1,57	1000600	EA-C416L/C	2,3 - 3,52,3	3,0480230DC20V o 32V		
0,2 - 0,98	2000	EA-C610LH/C	2,0 - 3,02,0	2,6600260DC20V o 32V		
0,5 - 1,76	1000600	EA-C618L/C	2,0 - 3,52,0	3,0600260DC20V o 32V		
0,69 - 2,35	750450	EA-C624L/C	2,6 - 4,02,6	3,5600260DC20V o 32V		
0,78 - 2,94	530300	EA-C630L/C	3,0 - 5,03,0	4,0600260DC20V o 32V		
0,49 - 1,18	2000	EA-C712LH/C	2,3 - 3,52,0	3,0700269DC20V o 32V		
0,59 - 2,25	1000600	EA-C723L/C	2,6 - 4,02,6	3,5700269DC20V o 32V		
0,98 - 3,14	750450	EA-C732L/C	3,0 - 5,03,0	4,5700269DC20V o 32V		
1,57 - 4,70	530300	EA-C748L/C	4,0 - 6,03,0	5,0700269DC20V o 32V		



Atornilladores preparados para trabajar con el controlador: Conexión de 7 pin

Arranque por empuje

Rango de Par ± 3%	Velocidad libre ± 10% (r.p.m.)	Modelo	Tornillo		Peso Largo mm	Alimentación
			Métrico	Auto roscante		
0,15 - 0,78	2000	EA-C408PH/C	1,6 - 3,01,6	2,6480230DC20V o 32V		
0,15 - 1,18	1000600	EA-C412P/C	1,6 - 3,01,6	2,6 480230DC20V o 32V		
0,3 - 1,57	1000600	EA-C416P/C	2,3 - 3,52,3	3,0480230DC20V o 32V		
0,2 - 0,98	2000	EA-C610PH/C	2,0 - 3,02,0	2,6600260DC20V o 32V		
0,5 - 1,76	1000600	EA-618P/C	2,0 - 3,52,0	3,0600260DC20V o 32V		
0,69 - 2,35	750450	EA-C624P/C	2,6 - 4,02,6	3,5600260DC20V o 32V		
0,78 - 2,94	530300	EA-C630P/C	3,0 - 5,03,0	4,0600260DC20V o 32V		
0,49 - 1,18	2000	EA-C712PH/C	2,3 - 3,52,0	3,0700270DC20V o 32V		
0,59 - 2,25	1000600	EA-C723P/C	2,6 - 4,02,6	3,5700270DC20V o 32V		
0,98 - 3,14	750450	EA-C732P/C	3,0 - 5,03,0	4,5700270DC20V o 32V		
1,57 - 4,70	530300	EA-C748P/C	4,0 - 6,03,0	5,0700270DC20V o 32V		



Atornilladores preparados para trabajar con el controlador: Conexión de 7 pin